

Straight Tongue Couplers



80050

Atwood's 2" ball couplers feature a patented high strength wrap around yoke with a sliding clamp for secure coupling. #80131 features self-adjusting ball clamp which automatically adjusts to slight variations in ball size.

Part No.	Ref. No.	Ball	Tongue Size	Finish	Capacity
80050	268000	2"	3" Square	Painted	3,500 lbs
80060	268100	2"	3" Square	Painted	5,000 lbs
80081	268400	2"	2" Square	Painted	5,000 lbs
80131	268800	2 5/16"	3" Square	Painted	8,500 lbs



2B2

BULLDOG® drop-forged couplers offer spring-loaded collars which provide positive-action coupling, ensuring a snug fit onto the hitch ball.

Part No.	Ref. No.	Ball	Tongue Size	Finish	Capacity
2B2	279400	2"	2 1/4" O.D. Round Shank	Painted	5,000 lbs
2B4	279600	2"	3" Square	Painted	5,000 lbs
2B5	279800	2"	3 1/2" Round	Painted	5,000 lbs
3B4	280100	2"	3" Square	Painted	7,000 lbs
4B2	280200	2 5/16"	2 1/4" O.D. Round Shank	Painted	12,500 lbs
4B4	280400	2 5/16"	3" Square	Painted	12,500 lbs



CP01-020

Zinc plated straight tongue couplers are ideal for marine, utility and cargo applications. Redline couplers are labeled, making them ideal for retail display.

Part No.	Ref. No.	Ball	Tongue Size	Finish	Capacity
CP01-010	264002	1 7/8"	2" Square	Zinc Plated w/ label	2,000 lbs
CP01-020	264004	1 7/8"	2 1/2" Square	Zinc Plated w/ label	2,000 lbs
CP01-030	264006	1 7/8"	3" Square	Zinc Plated w/ label	2,000 lbs
CP01-040	264010	2"	2" Square	Zinc Plated w/ label	3,500 lbs
CP01-050	264012	2"	2 1/2" Square	Zinc Plated w/ label	3,500 lbs
CP01-060	264014	2"	3" Square	Zinc Plated w/ label	3,500 lbs
CP01-070	264020	2"	3" Square	Zinc Plated w/ label	5,000 lbs



5144

Shelby's "Posi-Lock" trigger action mechanism clamps and releases the ball for fast, easy and secure hookups.

Part No.	Ref. No.	Ball	Tongue Size	Finish	Capacity
5143	262700	1 7/8"	2" Square	Oily	2,000 lbs
5141	262710	1 7/8"	2 1/2" Square	Oily	2,000 lbs
5144	262720	1 7/8"	3" Square	Oily	2,000 lbs
5145	262730	2"	2" Square	Oily	3,500 lbs
5142	262740	2"	2 1/2" Square	Oily	3,500 lbs
5146	262750	2"	3" Square	Oily	3,500 lbs
5175	262775	2"	3" Square	Oily	5,000 lbs



22300

The Fas-Lok® latching mechanism on these Fulton® brand couplers permit quick and easy trailer hook-up, and is factory adjusted for end-user convenience. A coupler lock hole is provided for additional trailer security. Ball clamp assemblies are serviceable for in-field replacement.

Part No.	Ref. No.	Ball	Tongue Size	Finish	Capacity
11200	265505	1 7/8"	2" Square	Oily	2,000 lbs
22200	265515	2"	2" Square	Oily	3,500 lbs
22250	265517	2"	2 1/2" Square	Oily	3,500 lbs
22300	265519	2"	3" Square	Oily	3,500 lbs

For Coupler Security Locks and Brackets See Page K-10 & K-11



“Yard Dog” Straight Tongue Coupler

As tough as it's name, the “Yard Dog” coupler design has been popular in the rental industry for many years. This weldable coupler is made of 1030 cast steel.

Part No.	Ref. No	Ball	Tongue Size	Finish	Capacity
WFH3	267300	1 7/8" & 2"	2" Square	Painted	7,500 lbs
WFH3RK	267345	Latch repair kit for WFH3			



A-Frame Couplers



Atwood's A-Frame Couplers are available with their patented wraparound yoke style (A), a thumb latch style (B), or with a trigger style (C) locking mechanism. The #82680 undermount coupler, which has a thumb latch style locking mechanism, is widely used in the mobile home industry.

Part No.	Ref. No.	Ball	Style	Tongue Size	Finish	Capacity
80071	268200	2"	A	50° A-Frame	Painted	5,000 lbs
88555	268250	2"	C	50° A-Frame	Painted	8,000 lbs
80101	268600	2 5/16"	A	50° A-Frame	Painted	8,500 lbs
81911	269000	2 5/16"	B	50° A-Frame	Painted	10,000 lbs
82680	269200	2 5/16"	D	50° A-Frame Undermount	Painted	13,000 lbs
64-4102	269100	2 5/16"	C	50° A-Frame	Painted	10,000 lbs
88050	267840	2"	Latch Repair Kit for Franklin 64-4103/Atwood Marvel 88000			
88061	267853	2 5/16"	Latch Repair Kit for Franklin 64-4102/Atwood Marvel 88007			



See Page F-5 for additional latch repair kits.



BULLDOG® drop-forged couplers offer spring-loaded locking collars which provide positive-action coupling, ensuring a snug fit onto the hitch ball. Tongue size is 50° A-Frame.

Part No.	Ref. No.	Ball	Latch	Finish	Capacity
2B8	280000	2"	Low-Profile	Painted	5,000 lbs
3B8	280120	2"	Low-Profile	Painted	7,000 lbs
4B8L	280590	2 5/16"	Low-Profile	Painted	12,500 lbs
4B8	280600	2 5/16"	Hi-Profile	Painted	12,500 lbs



Shelby's "Posi-Lock" trigger action mechanism clamps and releases the ball for fast, easy and secure hookups.

Part No.	Ref. No.	Ball	Tongue Size	Finish	Capacity
5172	262800	2"	50° A-Frame	Oily	5,000 lbs
5104	262810	2 5/16"	50° A-Frame	Painted	10,000 lbs




Fulton® A-Frame stamped couplers have high strength steel housings and are designed to weld onto frame members set at 50-degree angles. Stamped coupler 44305R features the Wedge-Latch™ replaceable ball clamp assembly. Part number 44150W is a cast steel coupler with the Wedge-Latch™ design, and has a cast shield to prevent latch damage.

Part No.	Ref. No.	Ball Size	Finish	Capacity
33305-P	266680	2"	Prime	5,000 lbs
44305R-P	266692	2 5/16"	Prime	10,000 lbs
44150W	266700	2 5/16"	Prime Cast	15,000 lbs



JACKS,
COUPLERS &
WINCHES

3" Adjustable Pintle Eye



18128

Expect a long service life from this high quality forged pintle eye. Inside diameter of the ring is 3" and ring thickness is 1 5/8".

Part No.	Ref. No.	Description	Capacity
18128	305600	Eye, w/ 4 hole bracket and bolts	12,000 lbs
18128XL	305650	Eye, w/ 6 hole bracket and bolts	12,000 lbs
16137	305810	Eye only for 18128, 18128XL	20,000 lbs

3/4" Adjustable Clevis



9095

This forged clevis provides more strength than a cast equivalent. The black powder coat finish also resists rust and corrosion. Takes a 3/4" diameter hitch pin, such as 34H on page K-7.

Part No.	Ref. No.	Description	Capacity
9095	305700	Clevis, w/ 4 hole bracket and bolts	12,000 lbs
9095XL	305750	Clevis, w/ 6 hole bracket and bolts	12,000 lbs
8979	305815	Clevis only for 9095, 9095XL	12,000 lbs

JACKS,
COUPLERS &
WINCHES

1 7/8" & 2" Adjustable Tongue Couplers



WFAH3-A

WFH3LA

Keep Your Equipment Safe – Protect It With A "Yard Dog"!

As tough as it's name, the "Yard Dog" Coupler design has been popular in the Rental Industry for many years. The forged coupler housing is virtually indestructible.

Part No.	Ref. No.	Description	Capacity
WFAH3	267305	Coupler only, (no bolts)	7,500 lbs
WFAH3-A	267310	Coupler Assembly, w/ 4 hole bracket and bolts	7,500 lbs
WFAH3-AXL	267315	Coupler Assembly, w/ 6 hole bracket and bolts	7,500 lbs
WFH3LA	267335	Ring to ball coupler adapter, fits 2 1/2" & 3" I.D. Pintle Eye	3,500 lbs
WFH3RK	267345	Latch repair kit for WFH3, WFAH3	

2" Adjustable Tongue Couplers



3B6M

The BULLDOG® brand features the only automatic and continuously tight ball fit in the industry. An adjustable coupler assures level operation for trailers when pulled by a variety of different vehicles.

Part No.	Ref. No.	Description	Capacity
3B6M	305824	BULLDOG® Coupler, w/ bolts for 1040, 1040XL	7,000 lbs
1040	305806	BULLDOG® Coupler, w/ 4 hole bracket and bolts	7,000 lbs
1040XL	305807	BULLDOG® Coupler, w/ 6 hole bracket and bolts	7,000 lbs

2 5/16" Adjustable Tongue Couplers

These couplers permit adjustment of the hitch height of the trailer, which allows the trailer to be towed by different vehicles. Atwood is equipped with Grade 8 bolts, while Bulldog, Wallace Forge and Fulton use Grade 5 bolts. Always follow manufacturer's recommendations for torque requirements.

Part No.	Ref. No.	Manufacturer	Bracket	Bolts/Nuts	Capacity
2425160	305819	Wallace Forge	None	Yes	14,000 lbs
A256C	305660	Fulton	4 Hole	Yes	12,000 lbs
A256CXL	305665	Fulton	6 Hole	Yes	12,000 lbs
A256	305828	Fulton	None	Yes	14,000 lbs
80281	305821	Atwood	None	Yes	12,000 lbs
80281C	305801	Atwood	4 Hole	Yes	12,000 lbs
80281CXL	305804	Atwood	6 Hole	Yes	12,000 lbs
4B6M	305826	Bulldog	None	Yes	12,500 lbs
1051	305808	Bulldog	4 Hole	Yes	12,000 lbs
1051XL	305809	Bulldog	6 Hole	Yes	12,000 lbs
WFAH4	267320	Wallace Forge "Yard Dog"	None	No	12,000 lbs
WFAH4-A	267325	Wallace Forge "Yard Dog"	4 Hole	Yes	12,000 lbs
WFAH4-AXL	267330	Wallace Forge "Yard Dog"	6 Hole	Yes	12,000 lbs

Replacement Parts		
Part No.	Ref. No.	Description
9093	305830	Grade 5 Mounting Bolt 5/8" x 4 1/2" for Wallace Forge & Bulldog
6-38	078800	5/8" Locknut for Wallace Forge & Bulldog
8978	306000	4 - hole channel bracket for all, 12K
8978XL	306025	6 - hole channel bracket for all, 12K
80299	305835	Mounting bolt 5/8" x 4 1/2" Grade 8 for Atwood
58LW	305840	5/8" Lockwasher for Atwood
58LN-GR5	305845	5/8" - 11 Hex Locknut, GR5 for Atwood



JACKS,
COUPLERS &
WINCHES

FULTON



A256



2425160

**WALLACE
FORGE
COMPANY**
Quality Since 1942



WFAH4-A

Redline Packaged Coupler Latch Repair Kits

Trailer towing with a worn or broken coupler is dangerous. Worn or broken couplers should be replaced or repaired. Redline Kits are packaged for showroom display.

Redline
TRAILER REPAIR PARTS

Part No.	Ref. No.	Manufacturer	Coupler Style	Ball
CP02-010	264050	Atwood	Yoke Style	2"
CP02-020	264055	Atwood	80131, 80281	2 5/16"
CP02-030	264060	Atwood	Trigger style A-Frame	2"
CP02-040	264070	Shelby	Posi-Lock, Class 1	1 7/8"
CP02-050	264075	Shelby	Posi-Lock, Class 2	2"
CP02-060	264080	Shelby	Posi-Lock, Class 3	2"
CP02-090	264100	Fulton	Handwheel (308)	2"
CP02-110	264120	Bulldog	High profile handle	All
CP02-120	264125	Bulldog	Pin & retainer	All

